

East Building, PHH-30 1200 New Jersey Avenue S.E. Washington, D.C. 20590

Pipeline and Hazardous Materials Safety Administration

DOT-SP 14770 (FIRST REVISION)

1. GRANTEE: (See individual authorization letter)

2. PURPOSE AND LIMITATION:

- a. This special permit authorizes the transportation in commerce of an organometallic substance, solid, water-reactive, flammable n.o.s in a non-DOT specification portable tank which is designed in accordance with the provisions for an UN portable tank (portable tank instruction "T9"), except it is equipped with a bottom opening. This special permit provides no relief from the Hazardous Materials Regulations (HMR) other than as specifically stated herein.
- b. The safety analyses performed in the development of this special permit only considered the hazards and risks associated with the transportation in commerce.
- c. Unless otherwise stated herein, this special permit consists of the special permit authorization letter issued to the grantee together with this document.
- 3. REGULATORY SYSTEM AFFECTED: 49 CFR Parts 106, 107 and 171- 180.
- 4. REGULATIONS FROM WHICH EXEMPTED: 49 CFR § 173.242 in that a non-DOT specification portable tank is not authorized, except as provided herein.
- 5. BASIS: This special permit is based on the application of $\overline{\text{Dow Chemical Company}}$ dated August 28, 2008 submitted in accordance with § 107.105 and the public proceeding thereon.

6. HAZARDOUS MATERIALS (49 CFR § 172.101):

Hazardous Materials Description			
Proper Shipping Name	Hazard Class/ Division	Identifi cation Number	Packing Group
Organometallic substance, solid, water-reactive, flammable n.o.s. (mixture containing aluminum alkyls)	4.3	UN3396	I

7. SAFETY CONTROL MEASURES:

- a. PACKAGING Packaging prescribed is a non-DOT specification portable tank which is designed in accordance with the provisions for an UN portable tank (portable tank instruction "T9"), except it is equipped with a bottom opening. The portable tank conforms to the configuration and typical dimensions shown on the Silvan Industries Inc. drawing 134-699 on file with the Office of Hazardous Materials Special Permits and Approvals. Additionally, the portable tank must be designed, manufactured and ASME Code "U" stamped with the following characteristics:
 - Minimum wall thickness: 0.250 inch.
 - Maximum allowable working pressure (MAWP): 175 psig.
 - Maximum capacity: 120 gallons (454 liters).
 - Rupture disc pressure relief valve (PRV) setting: Set at MAWP.
 - Maximum loading or discharge pressure: 100 psig.
 - Shape: cone-shaped funnel bottom with ball valve.
- b. $\underline{\text{TESTING}}$ Each portable tank must be tested, retested, and inspected as specified in § 180.600 (Subpart G) for UN portable tanks.

c. OPERATIONAL CONTROLS -

- (1) The 1 inch bottom ball valve must have a locking pin and be protected from impact during transportation.
- (2) A dry nitrogen blanket of 15 psig must be provided for transportation.

8. SPECIAL PROVISIONS:

- a. A person who is not a holder of this special permit who receives a package covered by this special permit may reoffer it for transportation provided no modification or change is made to the package or its contents and it is reoffered for transportation in conformance with this special permit and the HMR.
- b. A current copy of this special permit must be maintained at each facility where the package is offered or reoffered for transportation.
- c. Each portable tank must be plainly and durably marked "DOT-SP 14770" as specified in §§ 172.302(b) and (c).
- 9. MODES OF TRANSPORTATION AUTHORIZED: Motor vehicle, cargo vessel, and rail freight.
- 10. MODAL REQUIREMENTS: A current copy of this special permit must be carried aboard each cargo vessel or motor vehicle used to transport packages covered by this special permit.
- 11. <u>COMPLIANCE</u>: Failure by a person to comply with any of the following may result in suspension or revocation of this special permit and penalties prescribed by the Federal hazardous materials transportation law, 49 U.S.C. 5101 <u>et seq</u>:
 - o All terms and conditions prescribed in this special permit and the Hazardous Materials Regulations, 49 CFR Parts 171-180.
 - o Persons operating under the terms of this special permit must comply with the security plan requirement in Subpart I of Part 172 of the HMR, when applicable.

o Registration required by § 107.601 $\underline{\text{et seq.}}$, when applicable.

Each "Hazmat employee", as defined in § 171.8, who performs a function subject to this special permit must receive training on the requirements and conditions of this special permit in addition to the training required by §§ 172.700 through 172.704.

No person may use or apply this special permit, including display of its number, when this special permit has expired or is otherwise no longer in effect.

Under Title VII of the Safe, Accountable, Flexible, Efficient Transportation Equity Act: A Legacy for Users (SAFETEA-LU)—"The Hazardous Materials Safety and Security Reauthorization Act of 2005" (Pub. L. 109-59), 119 Stat. 1144 (August 10, 2005), amended the Federal hazardous materials transportation law by changing the term "exemption" to "special permit" and authorizes a special permit to be granted up to two years for new special permits and up to four years for renewals.

12. REPORTING REQUIREMENTS: Shipments or operations conducted under this special permit are subject to the Hazardous Materials Incident Reporting requirements specified in 49 CFR §§ 171.15 - Immediate notice of certain hazardous materials incidents, and 171.16 - Detailed hazardous materials incident reports. In addition, the grantee(s) of this special permit must notify the Associate Administrator for Hazardous Materials Safety, in writing, of any incident involving a package, shipment or operation conducted under terms of this special permit.

Issued in Washington, D.C.:

for Theodore L. Willke

Word By

Associate Administrator for Hazardous Materials Safety

Address all inquiries to: Associate Administrator for Hazardous Materials Safety, Pipeline and Hazardous Material Safety Administration, U.S. Department of Transportation, East Building PHH-30, 1200 New Jersey Avenue, Southeast, Washington, D.C. 20590.

November 17, 2008

Copies of this special permit may be obtained by accessing the Hazardous Materials Safety Homepage at http://hazmat.dot.gov/sp_app/special_permits/spec_perm_index.htm. Photo reproductions and legible reductions of this special permit are permitted. Any alteration of this special permit is prohibited.

PO: MAJORSL/am